

CLAIM AMENDMENTS

1. (Currently Amended) A hydraulic shock absorbing apparatus of a vehicle provided with hydraulic shock absorbers at right and left sides of a wheel, comprising:

a compression side damping force generating structure for mainly generating a compression side damping force is provided in ~~one~~ a first hydraulic shock absorber, an expansion side damping force generating structure for mainly generating an expansion side damping force is provided in ~~another~~ a second hydraulic shock absorber, and the generation of the compression side damping force and the expansion side damping force is ~~shared by the right and left~~ carried out substantially separately by the respective hydraulic shock absorbers,

the ~~one~~ first hydraulic shock absorber having

a vehicle body side tube and a wheel side tube which are slidably fitted to each other;

a damper having a damper cylinder and a piston rod in which a piston slidable within the damper cylinder is mountable to a leading end portion ~~thereof of the piston rod~~, and structured such that the damper cylinder is mountable to an inner side of the wheel side tube and the piston rod is mountable to an inner side of the vehicle body side tube;

a piston rod side oil chamber and a piston side oil chamber sectioned within the damper cylinder by the piston;

an oil reservoir chamber disposed in an outer periphery of the damper cylinder; and

two oil passages provided in the piston, a compression side damping valve being provided in ~~one of the oil passage-passages~~, and a check valve closing during compression and opening during expansion being provided in the other ~~of the oil passage-passages~~, and

wherein a volume compensating oil passage ~~of the piston rod~~ communicating the piston rod side oil chamber with the oil reservoir chamber is provided.

2. (Currently Amended) A hydraulic shock absorbing apparatus of a vehicle comprising:

a first and a second hydraulic shock absorbers provided ~~at both right and left sides of adjacent~~ a wheel;

each of the hydraulic shock absorbers comprising:

a vehicle body side tube and a wheel side tube being slidably fitted;

a damper constituted by a damper cylinder and a piston rod having a piston slidable within the damper cylinder, the piston being mountable to a leading end portion thereof, the damper cylinder being mountable to an inner side of the wheel side tube, the piston rod being mountable to an inner side of the vehicle body side tube;

a piston rod side oil chamber receiving the piston rod and a piston side oil chamber not receiving the piston rod are sectioned in both sides of the piston;

two oil passages communicating with the two oil chambers being provided in the piston;

an oil reservoir chamber for compensating a volume of the piston rod being provided in an outer periphery of the damper cylinder,

one of the hydraulic shock absorbers being provided with a compression side damping valve in one oil passage of the piston, and being provided with a check valve closing at the time of compression and opening at the time of expansion in another oil passage, and an oil passage for compensating a volume of the piston rod communicated with the oil reservoir chamber being provided in the piston rod side oil chamber,

wherein another of the hydraulic shock absorbers has an expansion side damping valve in one of the oil passage passages of the its piston, a check valve closing at the time of expansion and opening at the time of compression in another of the oil passage passages, and an oil passage for compensating the volume of the piston rod communicated with the oil reservoir chamber is disposed in the piston side oil chamber.

3. (Previously Presented) A hydraulic shock absorbing apparatus of a vehicle according to claim 1, wherein a bypass oil passage communicating the oil chambers in both sides of the piston is disposed in the piston rod of each of the hydraulic shock absorbers, and a damping force adjusting valve is disposed in the bypass oil passage.

4. (Currently Amended) A hydraulic shock absorbing apparatus of a vehicle according to claim 2, wherein a bypass oil passage communicating the oil chambers in both sides of the respective piston pistons is disposed in the piston rod of each of the hydraulic shock absorbers, and a damping force adjusting valve is disposed in the bypass oil passage.

5. (Previously Presented) A hydraulic shock absorbing apparatus of a vehicle according to claim 1, wherein the oil passage of the one hydraulic shock absorber is disposed in a side wall of the damper cylinder.
6. (Currently Amended) A hydraulic shock absorbing apparatus of a vehicle according to claim 2, wherein the oil passage of each of the one-hydraulic shock absorber absorbers is disposed in a side wall of the respective damper cylinder.
7. (Previously Presented) A hydraulic shock absorbing apparatus of a vehicle according to claim 3, wherein the oil passage of the one hydraulic shock absorber is disposed in a side wall of the damper cylinder.
8. (Currently Amended) A hydraulic shock absorbing apparatus of a vehicle according to claim 4, wherein the oil passage of each the ~~one-hydraulic shock absorber~~ absorbers is disposed in a side wall of the respective damper cylinder.
9. (Currently Amended) A hydraulic shock absorbing apparatus of a vehicle according to claim 1, wherein the oil passage of the ~~one-hydraulic shock absorber~~ provided for compensating the volume of the piston rod is disposed in a guide member for guiding the piston rod.
10. (Currently Amended) A hydraulic shock absorbing apparatus of a vehicle according to claim 2, wherein the oil passage of each of the one hydraulic shock absorbers provided for compensating the volume of the respective piston rod is disposed in a guide member for guiding the respective piston rod.
11. (Currently Amended) A hydraulic shock absorbing apparatus of a vehicle according to claim 3, wherein the oil passage of the ~~one-hydraulic shock absorber~~ provided for compensating the volume of the piston rod is disposed in a guide member for guiding the piston rod.
12. (Currently Amended) A hydraulic shock absorbing apparatus of a vehicle according to claim 4, wherein the oil passage of each of the one-hydraulic shock absorbers provided

for compensating the volume of the respective piston rod is disposed in a guide member for guiding the respective piston rod.

13. (New) A hydraulic shock absorbing apparatus of a vehicle provided with hydraulic shock absorbers at right and left sides of a wheel, comprising:

- a compression damping force hydraulic shock absorber having a compression side damping force generating structure for mainly generating a compression side damping force;

- a vehicle body side tube and a wheel side tube which are slidably fitted to each other;

- a damper having a damper cylinder and a piston rod in which a piston slidable within the damper cylinder is mountable to a leading end portion thereof, and structured such that the damper cylinder is mountable to an inner side of the wheel side tube and the piston rod is mountable to an inner side of the vehicle body side tube;

- a piston rod side oil chamber and a piston side oil chamber sectioned within the damper cylinder by the piston;

- an oil reservoir chamber disposed in an outer periphery of the damper cylinder;

- two oil passages provided in the piston, a compression side damping valve being provided in one of the oil passages, and a check valve closing during compression and opening during expansion being provided in the other of the oil passages, and

- a volume compensating oil passage communicating the piston rod side oil chamber with the oil reservoir chamber,

- the compression damping force hydraulic shock absorber being usable together with an expansion damping force hydraulic shock absorber,

- wherein compression damping and expansion damping is performed substantially separately by each of the respective shock absorbers.

14. (New) A hydraulic shock absorbing apparatus of a vehicle provided with hydraulic shock absorbers at right and left sides of a wheel, comprising:

- an expansion damping force hydraulic shock absorber having an expansion side damping force generating structure for mainly generating an expansion side damping force;

- a vehicle body side tube and a wheel side tube which are slidably fitted to each other;

a damper having a damper cylinder and a piston rod in which a piston slidable within the damper cylinder is mountable to a leading end portion of the piston rod, and structured such that the damper cylinder is mountable to an inner side of the wheel side tube and the piston rod is mountable to an inner side of the vehicle body side tube;

a piston rod side oil chamber and a piston side oil chamber sectioned within the damper cylinder by the piston;

an oil reservoir chamber disposed in an outer periphery of the damper cylinder; and

two oil passages provided in the piston, an expansion side damping valve being provided in one of the oil passages, and a check valve closing during expansion and opening during compression being provided in the other of the oil passages, and

a volume compensating oil passage communicating the piston rod side oil chamber with the oil reservoir chamber,

the expansion damping force hydraulic shock absorber being usable together with a compression damping force hydraulic shock absorber, wherein expansion damping and compression damping is performed substantially separately by each of the respective shock absorbers.